

SURTECH P-6253

A cationic polymer for coagulant applications

SURTECH P-6253 is a cationic carbamide resin useful in coagulant applications. It is recommended for use as a paint detackification treatment in paint spray booths, and as a demulsifier-coagulant for emulsified oily wastes.



Typical Properties

Specific Gravity	1.1
Solubility in water	Soluble
Viscosity @20°C – cps (Brookfield LVT –1 @30 rpm)	<100
Appearance and odor	Colorless, syrropy liquid with a slight formaldehyde
%Volitiles	50 after 14hrs. @ 105°C
pH	3.5-4.2
Boiling Point	100°C

Handling Precautions

SURTECH P-6253 is an irritant. Rubber gloves and safety goggles are required. Body-protective clothing and shoes are required. Eye-wash fountains and safety showers in the work area are required. See the **SURTECH P-6253** Material Safety Data Sheet for detailed health and safety information.

The information given herein is correct to the best of our knowledge. However, no warranty is expressed or implied regarding its accuracy or the results to be obtained from the use thereof and users should make their own tests to determine the suitability of these products for their own particular purpose. No statement in this brochure/leaflet is intended or should be construed as a recommendation to infringe any existing patent.

7/1/02

Surface Chemists of Florida, Inc.

1303 Park Lane South

Jupiter, FL 33458

561-745-8774

www.surfacechemists.com