

# SURTECH SBS-163

## An oil-soluble H<sub>2</sub>S scavenger

**Surtech SBS-163** removes hydrogen sulfide from reservoirs of metal-working fluids, and other systems where hydrogen sulfide or mercaptans present an environmental hazard.



### Typical Properties

Appearance:	viscous light yellow liquid with a mild odor
Specific gravity:	1.07
Solubility in Water:	insoluble
Viscosity @25°C – cps: (Brookfield LVT-3@6rpm)	5,000 – 10,000

### Directions for Use

For best results, **Surtech SBS-163** should be mixed in a 50/50 ratio with the cutting fluid base and added to the diluted fluid with good agitation. In this ratio, one quart of **Surtech SBS-163** will treat approximately 500 gallons of the cutting fluid, depending on the H<sub>2</sub>S concentration. When applied to high surface area media, **Surtech SBS-163** effectively removes H<sub>2</sub>S vapors from confined air spaces.

### Handling Precautions

**Surtech SBS-163** is a slight irritant. Rubber gloves, safety goggles, body-protective clothing and shoes are required. Eye-wash fountains and safety showers in the work area are also required. See the **Surtech SBS-163** Material Safety Data Sheet for detailed health and safety information.

The information given herein is correct to the best of our knowledge. However, no warranty is expressed or implied regarding its accuracy or the results to be obtained from the use thereof and users should make their own tests to determine the suitability of these products for their own particular purpose. No statement in this brochure/leaflet is intended or should be construed as a recommendation to infringe any existing patent.

5-01-01

**Surface Chemists of Florida, Inc.**

1303 Park Lane South

Jupiter, FL 33458

561-745-8774

[www.surfacechemists.com](http://www.surfacechemists.com)