

This formula demonstrates the use of **SURTECH CR-125** (a product of Surface Chemists of Florida, Inc.) as a Component of a liquid Graffiti Remover.

### Graffiti Remover (Microemulsion)

**Soil** – Acrylic Paints

**Surface** – Painted surfaces, Concrete, Ceramic tile

**Application Method** – Spray

**Manufacture** – Mix tank with propeller stirrer

---

| <b>Composition</b>                         | <b>% WT</b> | <b>Function</b>             |
|--|-------------|-----------------------------|
| <b>Surtech CR-125</b>                      | 1.5         | Emulsify/Coupler/Detergency |
| C <sub>8-10</sub> fatty acid methyl esters | 1.0         | Solvent                     |
| q. s. water                                |             |                             |

Directions for use: Apply the remover to surface, allow to stand for 2-5 minutes, rinse with a high pressure water spray.

NOTE: Information herein is accurate to the best of our knowledge. Suggestions are made without warranty or guarantee of results. Before using, the user should determine the suitability of the product for the intended use and user assumes the risk if liability in connection therewith. We do not suggest violation of any existing patents or give permission to practice any patented invention without a license.

**Surface Chemists of Florida, Inc.**

1303 Park Lane South • Jupiter, FL 33458

Tel. (561) 745-8774 • Fax (561) 745-8737

[www.surfacechemists.com](http://www.surfacechemists.com)